




- considerably prolong working life of lifting slings
- protects weight and sling against abrasion and cutting [sharp edges]



PUDF - Polyurethane corner protection


reference	technical data [mm]			
	l	h	a	b
PUDF025	250	80	25	10
PUDF035	250	80	35	10
PUDF055	300	100	55	10
PUDF060	450	100	60	30
PUDF070	450	120	70	30
PUDF080	450	120	80	30
PUDF090	470	130	90	40
PUDF100	470	150	100	40
PUDF110	470	150	110	40
PUDF130	470	170	130	40
PUDF160	470	200	160	40
PUDF200	470	240	200	40
PUDF220	470	240	220	40
PUDF250	500	280	250	40



suitable for textile lifting slings and cargo lashing

PUPP - Polyurethane corner protection - suitable for flat webbing slings

reference	technical data [mm]				
	L	B	Ba	H	Ha
PUPP030	100	40	50	10	20
PUPP060	100	70	80	12	30
PUPP090	100	100	110	12	30
PUPP120	100	135	145	12	30
PUPP150	150	160	170	12	30
PUPP180	150	190	200	12	30
PUPP240	200	280	300	15	40
PUPP300	200	320	340	20	45




PUKWS - Polyurethane corner protection, compact - suitable for wire ropes and chains

reference	technical data [mm]	
	d	l
PUKWS025	30	80
PUKWS040	50	125



PUKW - Polyurethane corner protection, compact - suitable for textile lifting slings

reference with / without magnets	technical data	
	l [mm]	magnets count
PUKW0025 / PUKW1025	25	2
PUKW0040 / PUKW1040	40	2
PUKW0065 / PUKW1065	65	2
PUKW0075 / PUKW1075	75	4
PUKW0100 / PUKW1100	100	4
PUKW0125 / PUKW1125	125	4
PUKW0150 / PUKW1150	150	4
PUKW0200 / PUKW1200	200	6
PUKW0300 / PUKW1300	300	8




PUSKK - Polyurethane corner protection, with metal joint - suitable for wire ropes and chains

reference	B	L	D diameter	S
PUSKK006	32	80	20	6
PUSKK008	44	95	27	8
PUSKK010	54	110	36	10
PUSKK013	65	140	46	13



PUSKB - Polyurethane corner protection with metal joint - for textile lifting slings


without/with/two magnets	technical data [mm]		
	B width	L	H
PUSKB0030 / PUSKB1030 / PUSKB2030	35	115	10
PUSKB0060 / PUSKB1060 / PUSKB2060	65	115	10
PUSKB0090 / PUSKB1090 / PUSKB2090	95	115	10
PUSKB0150 / PUSKB1150 / PUSKB2150	155	115	10



• we will help you select right protection for your lifting needs

PVC

PVC PROTECTIVE SLEEVES



Suitable sling protection for lifting of unmachined, dirty, and smooth weights. Suitable for roundslings and webbing slings [flat].

Features:

- work environment temperature from -10°C do $+60^{\circ}\text{C}$
- flexible PVC sleeve with PES reinforcement
- smooth inner and outer surface
- resistant to light abrasives, UV radiation, most chemicals
- supplied widths: 40, 50, 60, 70, 80, 100, 120, 160, 240, 320 mm

PVC sleeves application possibilities [necessary to specify in order]



TYPE 1



TYPE 3



TYPE 2



TYPE 4

Our reference: **PVC999**

Explanation:

- PVC** – PVC protective sleeve
- 999** – width [mm]

Ordering example:

DP030050 + PVC100, 2x1 m, type 3 1 pc

Above means:


we order 1 pc of roundsling, 100% PES, endless, load capacity 3000 kg, nominal length 5 m + PVC protective sleeve, width 100 mm, length 2x1 m, type 3

POLYURETHANE SURFACE COAT

- surface coating with polyurethane is available only for flat webbing slings on customer's special request
- polyurethane coat protect webbing sling against abrasives, cut and prevent liquids from soaking into webbing
- coating type: one-sided / two-sided

PU

POLYURETHANE SLEEVES AND CORNERS



Very appropriate protection for textile, chain and wire rope lifting slings. Suitable protection against sharp edges and cutting.

Features:

- work environment temperature from -40°C do $+100^{\circ}\text{C}$
- made from extremely sturdy plastic [polyurethane]
- handy when turning weight
- standard sleeve wall thickness is 5 mm
- metal reinforced protections on request

TYPES of PU sleeves

PU1 [one-sided]	PU2 [two-sided]	PU2D [two-sided, leading slot]	PULR
application			
for easy, fast and safe lifting	both sides of lifting sling can be used for lifting	fast end easy attachment and positioning on lifting sling	all sides of lifting sling can be used for lifting
possible positions on slings			
		all possible positions on lifting sling	fixed position on wire rope or chain sling
I = PU sleeves width			d = inner diameter
50, 60, 80, 110, 145, 170, 200, 290, 330 [mm]			12, 14, 15, 18, 20, 22, 26, 28, 32, 35, 42, 45, 50, 63, 75, 85, 120 [mm]
suitable for textile lifting slings			for wire ropes and chains

Our reference: **PU TYP 999**

Explanation:

- PU** – polyurethane protective sleeve
- TYP** – 1 – one-sided, 2 – two-sided, 2D – two-sided with leading slot
- 999** – width, diameter [mm]

Ordering example:

DP030050 + PU2080, 2x1 m, type 3 1 pc

Above means:

we order 1 pc of roundsling, 100% PES, endless, load capacity 3000 kg, nominal length 5 m + PU protective sleeve - two-sided, width 80 mm, length 2x1 m, type 3